



No.	Photo	Model	Product	Feature
1		15-5800VHT	5.8GHz 1W High Power Video + Audio Transmitter with Alarm	<ul style="list-style-type: none"> • 5.8 GHz 16 CH TX module • 1.0 W output • Transmits AV up to 800M (Light-of-sight) • ID addressing • 5dBi Antenna • Alarm Input • Support any camera and video signal
2		15-5800VR	5.8GHz Video + Audio Receiver with Alarm	<ul style="list-style-type: none"> • 5.8 GHz 8 CH RX module • Video scramble • ID addressing • 3dBi Antenna • Audio, Video, Alarm Output
3		15-AC24-1A	AC 24V to DC12V Converter	<ul style="list-style-type: none"> • Convert AC / DC 24V to DC 12V • DC12V / 800mA (Max) output
4		15-AC24-2A	AC 24V to DC 12V Converter	<ul style="list-style-type: none"> • Convert AC 24V to DC 12V for camera or car TFT monitor • DC 12V / 2,000mA output • Built-in power buffer
5		15-AH34B-HFI	External IP66 Camera Housing with Heater, Fan & IR LED	<ul style="list-style-type: none"> • Tempered glass viewing window • Die casting Al-Alloy construction • Built in heater and fan • IP66 water protection • 60M High power IR-LED • Suitable lens diameter: 40mm
6		15-AT003	All-in-one Toner & Probe Kit	<ul style="list-style-type: none"> • Locate cables quickly and easily • Locate hidden cables • Cable Tester
7		15-AU35M	3.5" LCD Color Test Monitor	<ul style="list-style-type: none"> • 320(H) x 240(V) Pixels • Coaxial cable quality test • CAT5 cable quality test • Remote OSD control • Video & Audio input, built in 0.5W speaker • DC 12V output for camera • Includes 2200mA Li-poly battery
8		15-AU45	Remote OSD Controller for R series camera	<ul style="list-style-type: none"> • Control remote OSD via coaxial cable • Distance up to 300M • For "R" series camera
9		15-AU50ES-2	Economic PTZ controller	<ul style="list-style-type: none"> • Multi-functional keys for iris, focus and zoom control • Support RS485 • Speed dome address range: 0 ~ 255
10		15-AU50H-2	3 Stage joystick PTZ controller	<ul style="list-style-type: none"> • Designed to control Inspire DVR and speed dome • 3 stage joystick • Support RS485 (RJ45 connector & terminal block) • Speed level adjustable • Individual key for each setting • Speed dome address range: 0 ~ 255
11		15-BA07	Audio Pick Up Box	<ul style="list-style-type: none"> • Additional mini microphone for all cameras • DC 12V
12		15-BA08	In Line Audio Pick Up Box	<ul style="list-style-type: none"> • In line additional mini microphone for all cameras • DC 12V
13		15-CA453C-2	Hi-Res Hi-Sensitive HDR Wide Dynamic Box Camera	<ul style="list-style-type: none"> • Super Hi-Res 1/3" CCD • 620 TVL • 0.001 Lux • Auto 3D-DNR more than 64dB • Super wide dynamic range 52dB • Built-in OSD menu • AC24V / DC12V dual power • Lens not included
14		15-CD02B	Mini Type Dome Housing	<ul style="list-style-type: none"> • Designed for COP mini type camera

15		15-CD03BS	Wall mount bracket for 15-CD51 series PTZ	<ul style="list-style-type: none"> • Designed for 15-CD51XXX series speed dome
16		15-CD04BT	Pole Mount Bracket	<ul style="list-style-type: none"> • Designed for 15-CD55TW series speed dome
17		15-CD35VA	1/3" Sony CCD Varifocal Dome Camera	<ul style="list-style-type: none"> • 1/3" Sony CCD • 2.8mm ~ 10mm varifocal lens • 420 TVL • 0.5 Lux • Auto tracking white balance • DC12V • No OSD
18		15-CD35VAI	1/3" Sony CCD Varifocal Dome Camera	<ul style="list-style-type: none"> • 1/3" Sony CCD • 2.8mm ~ 10mm varifocal lens • 420 TVL • 21PCS IR-LED (10M) • 0 Lux (IR-On) • Auto tracking white balance • DC12V • No OSD
19		15-CD48VB	1/3" Sony CCD Varifocal Vandal Dome Camera	<ul style="list-style-type: none"> • 1/3" Sony CCD • 2.8mm ~ 10mm varifocal lens • 550 TVL • 1 Lux • Auto tracking white balance • DC12V • No OSD
20		15-CD36VBI	1/3" Sony CCD Varifocal Dome Camera	<ul style="list-style-type: none"> • 1/3" Sony CCD • 4mm ~ 9mm varifocal lens • 420 TVL • 36PCS IR-LED (25M) • 0 Lux (IR-On) • Auto tracking white balance, Auto AES • Metal Housing • DC12V • No OSD
21		15-CD453VB-2	Hi-Res Hi-Sensitive HDR Wide Dynamic Varifocal Vandal Dome Camera	<ul style="list-style-type: none"> • Super Hi-Res 1/3" CCD • 3.7mm ~ 12mm Lens • 620 TVL • 0.01 Lux • Auto 3D-DNR more than 63dB • Super wide dynamic range 48dB • Built-in OSD menu (AES, DSS, BLC, etc) all adjustable • AC24V / DC12V dual power
22		15-CD455VBIC-2	Hi-Res Hi-Sensitive SDR Super Wide Dynamic Varifocal Vandal Dome Camera with IR-LED and IR-Cut	<ul style="list-style-type: none"> • Super Hi-Res 1/3" CCD • 3.7mm ~ 12mm Lens • 650 TVL • 24 PCS IR LED (30M) • 0 Lux (IR On) • Removable IR-Cut • Auto 3D-DNR more than 63dB • Super wide dynamic range 48dB • Built-in OSD menu (AES, DSS, BLC, etc) all adjustable • DC12V
23		15-CM453VIC	Hi-Res Hi-Sensitive HDR Wide Dynamic Varifocal Bullet Camera with IR-LED	<ul style="list-style-type: none"> • Super Hi-Res 1/3" CCD • 3.7mm ~ 12mm Lens • 620 TVL • 42PCS IR-LED (40M) • 0 Lux (IR-On) • Removable IR-Cut • Auto 3D-DNR more than 63dB • Super wide dynamic range 48dB • Built-in OSD menu (AES, DSS, BLC, etc) all adjustable • AC24V / DC12V dual power
24		15-CD501PTZ-2	Wall Mount 100X PTZ Dome	<ul style="list-style-type: none"> • 1/4" CCD • 3.8mm ~ 38mm auto iris lens • 570 TVL • 0.7 Lux (Color); 0.02 Lux (B/W) • 10X optical zoom, 10X digital zoom • Removable IR-Cut filter • 64 preset points, 4 cruising tracks, 4 swings, 1 pattern

25		15-CD51PTZ	100X Mini Speed Dome	<ul style="list-style-type: none"> • 1/4" CCD • 3.7mm ~ 37.8mm auto iris lens • 480 TVL • 0.03 Lux (ICR ON) • 10X optical zoom, 10X digital zoom • Removable IR-Cut filter • 32 preset points, 6 cruising tracks
26		15-CD512HW-2	192X Mini Outdoor Speed Dome	<ul style="list-style-type: none"> • 1/4" CCD • 3.9mm ~ 46mm auto iris lens • 680 TVL • 0.2 Lux (Color); 0.02 Lux (B/W) • 12X optical zoom, 16X digital zoom • 127 preset points, 8 Cruising tracks, 8 Swings, 4 Patterns • 8 Privacy zone • 4 Alarm-In • IP66 Water proof
27		15-CD55TW-1020-2	432X Outdoor High Speed Dome	<ul style="list-style-type: none"> • Sony FCB-EX1020P Zoom module • 3.4 ~ 122.4mm • 550 TVL • 0.1 Lux (Color), 0.01 Lux (B/W) • 36X optical zoom, 12X Digital zoom • 220 Preset points, 8 Cruising tracks, 8 Swings, 8 Patterns • 8 Privacy zone • 6 Alarm-In, 2 Alarm-Out • IP66 Water proof
28		15-CG36	Color Pin-Hole Camera in Metal Housing	<ul style="list-style-type: none"> • 1/3" Sony Super HAD II CCD • 3.7mm pin hole lens • 420 TVL • 0.01 Lux • Auto Gain Control, Auto White Balance • Size 36mm X 36mm
29		15-CG453/CG43	Hi-Res Starlight Color Mini Camera with C/CS mount	<ul style="list-style-type: none"> • 1/3" Hi-Res CCD • 3.6mm Lens • 600 TVL • 0.001 Lux • Auto 3D-DNR more than 64dB • Super wide dynamic range 52dB • Built-in OSD menu • 2X digital zoom • DC12V
30		15-CG55H	Hi-Res Color Mini Camera	<ul style="list-style-type: none"> • 1/4" Sony Super HAD CCD • 3.6mm or CS mount lens • 480 TVL • 0.05 Lux • Auto Gain Control, Auto White Balance • Size 37.5mm X 39mm
31		15-CM25I	Color DSP Finger Camera	<ul style="list-style-type: none"> • 1/3" Sony Super HAD CCD • 4mm Lens • 420 TVL • 23PCS IR-LED • 0 Lux (IR-On) • Auto Gain Control, Auto White Balance • DC12V • No OSD • IP66 metal housing
32		15-CM26CM-2	CMOS Color Tube Camera with IR LED	<ul style="list-style-type: none"> • 1/4" CMOS Sensor • 6mm Lens • 480 TVL • 4PCS IR-LED • 0 Lux (IR-On) • Auto Gain Control, Auto White Balance • DC12V • No OSD • Cable length: 30cm
33		15-CM36I	All-in-One Camera with IR LED	<ul style="list-style-type: none"> • 1/3" Sony CCD • 420 TVL • 6mm Lens • 72PCS IR-LED (30M) • 0 Lux (IR-On) • Auto electric shutter, auto tracking white balance • Metal outdoor housing • DC12V • No OSD

34		15-CM36VI	Varifocal All-in-One Camera with IR LED	<ul style="list-style-type: none"> • 1/3" Sony CCD • 420 TVL • 4mm ~ 9mm Lens • 72PCS IR-LED (30M) • 0 Lux (IR-On) • Auto electric shutter, auto tracking white balance • Metal outdoor housing • DC12V • No OSD
35		15-CM371-2 (Replaced by 15-CM36I)	All-in-One Camera with IR LED	<ul style="list-style-type: none"> • 1/3" Sony CCD • 420 TVL • 6mm Lens • 72PCS IR-LED (30M) • 0 Lux (IR-On) • Auto electric shutter, auto tracking white balance • Metal outdoor housing • DC12V • No OSD
36		15-CM37VI-2 (Replaced by 15-CM36VI)	Varifocal All-in-One Camera with IR LED	<ul style="list-style-type: none"> • 1/3" Sony CCD • 420 TVL • 4mm ~ 9mm Lens • 72PCS IR-LED (30M) • 0 Lux (IR-On) • Auto electric shutter, auto tracking white balance • Metal outdoor housing • DC12V • No OSD
37		15-CM48VIC-2	Hi-Res Varifocal Bullet Camera with IR-Led and IR-Cut	<ul style="list-style-type: none"> • 1/3" Sony Hi-Res CCD • 520 TVL • 3.5mm ~ 8mm lens • 76PCS IR-LED (45M) • 0 Lux (IR-On) • Auto electric shutter, auto tracking white balance • Removeable IR filter • Outdoor housing • No OSD • DC12V
38		15-CW25M-2	Automobile Weather Proof Camera	<ul style="list-style-type: none"> • 1/3" CCD Sensor • 420 TVL • 3.6mm Lens • 0.05 Lux • Mirror image for automobile • DC12V
39		15-CZ40HC-2	100X Power Zoom Camera	<ul style="list-style-type: none"> • 1/4" Interline transfer CCD • 570 TVL • 0.02 Lux (B/W) • 3.8mm ~ 38mm Lens • 10X optical zoom, 10X digital zoom • Removable IR Filter • RS485 Control • DC12V
40		15-CZ55HC-2	230X Power Zoom Camera	<ul style="list-style-type: none"> • 1/4" Interline transfer CCD • 580 TVL • 0.01 Lux (B/W) • 3.6mm ~ 82.8mm Lens • 23X optical zoom, 10X digital zoom • Removable IR Filter • RS485 Control • DC12V
41		15-CO502IC	230X Power Zoom Camera with IR-LED	<ul style="list-style-type: none"> • 1/4" Sony HAD CCD • 480 TVL • 10PCS high power LED (100M) • 0 Lux (IR-On) • 3.8mm ~ 87.4mm Lens • 23X optical zoom, 10X digital zoom • Removable IR Filter • RS485 Control • IP66 Water proof • DC12V
42		15-CM46VIC	Varifocal All-in-One Camera with IR-LED	<ul style="list-style-type: none"> • 1/3" Sony HAD CCD • 550 TVL • 4mm ~ 9mm Lens • 72PCS of IR-LED • 0 Lux (IR-On) • Auto electric shutter, auto tracking white balance • No OSD • Metal Housing

43		15-DA01-2	VGA to Composite Converter	<ul style="list-style-type: none"> • Support PC resolution up to 1024 X 768 @ 72Hz • Brightness, contract and sharpness adjustable • Support composite and S-Video ouput • Plug & Play
44		15-IL10	High Power IR-LED (100M)	<ul style="list-style-type: none"> • IP66 Water proof • 14PCS of 850nm high power IR-LED • Distance: 100M @ 45° • AC24V
45		15-IL15	High Power IR-LED (150M)	<ul style="list-style-type: none"> • IP66 Water proof • 14PCS of 850nm high power IR-LED • Distance: 150M @ 45° • AC24V
46		15-L0550DIRS	5mm ~ 50mm Varifocal Lens	<ul style="list-style-type: none"> • Focal Length: 5mm ~ 50mm • Auto iris, DC Drive • IR correction coating • CS Mount
47		15-L0560ZDK	5mm ~ 60mm Varifocal Lens	<ul style="list-style-type: none"> • Focal Length: 5mm ~ 60mm • Auto iris, DC Drive • CS Mount
48		15-L2812ZD	2.8mm ~ 12mm Varifocal Lens	<ul style="list-style-type: none"> • Focal Length: 2.8mm ~ 12mm • Auto iris, direct drive • CS Mount
49		15-MC07-2	7" TFT LCD Color Monitor	<ul style="list-style-type: none"> • Resolution: 1440 X 234 • Screen ratio: 16 : 9 • With remote control
50		15-PSD1009-2	DC12V 9 ports Power Supply	<ul style="list-style-type: none"> • Input voltage: AC100V ~ AC240V @ 60/50Hz • Output voltage: DC12V +/- 5% • Resetable RTC fuse • Fuse rating: 2A • Total output current: 10A • Total outputs: 9
51		PS4000BP-2	DC12V 4000mA Battery Pack	<ul style="list-style-type: none"> • DC12V, 4000mAh output • Battery switch for charge managemet • Battery weight: 155g
52		PS9000BP-2	DC12V 9000mA Battery Pack	<ul style="list-style-type: none"> • DC12V, 9000mAh output • Battery switch for charge managemet • Battery weight: 375g
53		15-U101D	BNC to RJ45 Video Balun with Data	<ul style="list-style-type: none"> • Built in 2KV surge protect • Built in 15KV electrostatic discharge • BNC and H termal to RJ45 jack • Max distance: 300M (Color), 600M (B/W) • Passive type